



Life in Light

MEGAMAN®

LED MR16

Model No.:

ER2508dLN-WFL

Voltage (V):

AC/DC12V

Wattage (W):

8.0



Lamp Base	Lamp Life (hrs)	Diameter (mm)	Length (mm)	Rated Luminous Flux (lm)	Beam Angle (°)	Max. Luminous Intensity	Colour Rendering Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 100% of the Full Light Output(sec)	Switching Cycles (times)	Colour Consistency (SDCM)	Lumen Maintenance at the End of Lamp Life (%)	Energy Label (EEL)
				lm		cd	CRI	PF				SDCM	(%)	
Warm White (2800K)														
GU5.3	25,000	50	51	450	36	1600	82	>0.50	<0.5	Instant full light	>1,000,000	<6	≥90	A
Cool White (4000K)														
GU5.3	25,000	50	51	450	36	1600	85	>0.50	<0.5	Instant full light	>1,000,000	<6	≥90	A



Operating Temperature (°C) :

-30 to +40




Mercury Content (mg):


N/A



DIMMERABLE®

Linear Dimming
100%
Dims on Dimmer Switches

LED MR16



Conventional MR16

Spectral power distribution

2800K

4000K

